

# Fast Logic Delayed Pulse Generator


SERIES: **DPG-41**

T<sup>2</sup>L Interfaced  
8 pin DIP



**Features:**

- Low Cost.
- Completely Interfaced for TTL.
- Low profile.
- Fits standard 8 pins DIP socket.



**Specifications:**

- Delay tolerance: see table.
- Rise-time: 2 ns typ.
- Minimum pulse width: 10 ns.
- Temperature range: 0°C to + 70°C.  
(-55°C to + 125°C on request)\*
- Temperature coefficient: 100 PPM/°C.
- Supply voltage: 4.75 to 5.25 Vdc.
- Input signal requirement: TTL logic.
- Output fan-out: TTL Schottky loads.
- Power dissipation: 225 mw typ.

\*Add "M" after Part No. Example: DPG-41-10-25M

Part Number	Pulse Width (In ns)
DPG-41-( )-5	5 ± 1
DPG-41-( )-6	6 ± 1
DPG-41-( )-7	7 ± 1
DPG-41-( )-8	8 ± 1
DPG-41-( )-9	9 ± 1
DPG-41-( )-10	10 ± 1
DPG-41-( )-15	15 ± 1
DPG-41-( )-20	20 ± 1
DPG-41-( )-25	25 ± 1
DPG-41-( )-30	30 ± 1
DPG-41-( )-35	35 ± 1
DPG-41-( )-40	40 ± 1.5
DPG-41-( )-45	45 ± 1.5
DPG-41-( )-50	50 ± 1.5
DPG-41-( )-60	60 ± 1.5
DPG-41-( )-70	70 ± 2
DPG-41-( )-75	75 ± 2
DPG-41-( )-80	80 ± 2
DPG-41-( )-90	90 ± 3
DPG-41-( )-100	100 ± 3

Note: Insert delay time in the P/N.  
Ex. DPG-41-30-35.

