


Fast Logic
**Multiple Digital
 Delay Units**

SERIES: MDU-4F
 (14 pins DIP) TTL Interfaced



Features:

- Completely interfaced for TTL & DTL application.
- P.C. board space economy achieved.
- Fits standard 14 pins DIP socket.
- 4 equal delay units/package.



Specifications:

- Delay Tolerance: $\pm 5\%$ or 2 ns whichever is greater.
- Rise-time: 2 ns typically.
- Temperature coefficient: 100 PPM/ C.
- Temperature range: 0° to + 70 C.
- Supply voltage: 5 Vdc $\pm 5\%$.
- Supply Current:
 I_{cc1}: 110 ma.
 I_{ccH}: 24 ma.
- DC parameters: See TTL-Fast Schottky Logic Table on Page 6.

Test Conditions:

- Input Pulse Width: $\approx 150\%$ of total delay.
- Time delay measured @ 1.5 V on rising edge.
- Rise-time is measured from .75 V to 2.4 V of leading time
- All measurements made @ V_{cc} = 5V;
 T_A = +25°C.

Part No.	Delay Per Line (ns)
MDU-4F-5	5
MDU-4F-10	10
MDU-4F-15	15
MDU-4F-20	20
MDU-4F-25	25
MDU-4F-30	30
MDU-4F-35	35
MDU-4F-40	40
MDU-4F-45	45
MDU-4F-50	50

Other delay times available on request.

